

SAFETY DATA SHEET

Date of issue: 05/06/2015
Revised: 05/06/2015

Section 1: Identification

Trade name: MATTE CLEAR
Product code: GB00160101
Product category: PC9a Paints and coatings.
Manufacturer/Supplier: Grabber Construction Products
5255 West 11000 North
Highland, Utah 1-800-477-TURN
www.grabberman.com
Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.

Section 2: Hazard(s) Identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.
Press. Gas H280 Contains gas under pressure; may explode if heated.
Carc. 2 H351 Suspected of causing cancer.
Repr. 2 H361 Suspected of damaging fertility or the unborn child.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

GHS Hazard pictograms



Signal word Hazard statements

Precautionary statements

Danger
Extremely flammable aerosol.
Contains gas under pressure; may explode if heated. Causes skin irritation.
Causes serious eye irritation. Suspected of causing cancer.
Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
Obtain special instructions before use.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection. Do not handle until all safety precautions have been read and understood. Wear protective gloves.
Do not breathe dust/fume/gas/mist/vapors/spray.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a poison center/doctor if you feel unwell.
If skin irritation occurs: Get medical advice/attention. If on skin: Wash with plenty of water.
If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container in accordance with local/regional/national/international regulations.

Line
Saver

Section 3: Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description:

This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
67-64-1	Acetone	21.76%
74-98-6	propane	13.87%
108-21-4	isopropyl acetate	13.36%
108-10-1	methylisobutyl ketone	10.36%
106-97-8	n-butane	8.15%
64-17-5	ethyl alcohol	6.22%
108-88-3	Toluene	6.13%
111-76-2	Glycol Ether EB	5.07%
78-93-3	methylethyl ketone	2.73%
67-63-0	isopropyl alcohol	1.24%

Section 4: First-Aid Measures

After inhalation:

Supply fresh air; consult doctor in case of complaints.

After skin contact:

Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects:

Dizziness

Indication of any immediate medical attention needed:

No further relevant information available.

Section 5: Fire-Fighting Measures

Extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with waterspray.

Special hazards:

Can form explosive gas-air mixtures.

Protective equipment for firefighters:

A respiratory protective device may be necessary.

Section 6: Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills with inert absorbent material. Refer to section 13 for disposal information. Dispose contaminated material as waste according to section 13.

Section 7: Handling and Storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

Section 8: Exposure Controls/Personal Protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m ³ , (500) NIC-250 ppm BEI

74-98-6 propane

PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm refer
TLV (USA)	to Appendix F

108-21-4 isopropyl acetate

PEL (USA)	Long-term value: 950 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: 836 mg/m ³ , 200 ppm Long-term value: 418 mg/m ³ , 100 ppm

108-10-1 methyl isobutyl ketone

PEL (USA)	Long-term value: 410 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm
TLV (USA)	Short-term value: 307 mg/m ³ , 75 ppm Long-term value: 82 mg/m ³ , 20 ppm BEI

106-97-8 n-butane

REL (USA)	Long-term value: 1900 mg/m ³ , 800 ppm
TLV (USA)	Short-term value: 2370 mg/m ³ , 1000 ppm

64-17-5 ethyl alcohol

PEL (USA)	Long-term value: 1900 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV (USA)	Short-term value: 1880 mg/m ³ , 1000 ppm

108-88-3 Toluene

PEL (USA)	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 75 mg/m ³ , 20 ppm BEI

111-76-2 Glycol Ether EB

PEL (USA)	Long-term value: 240 mg/m ³ , 50 ppm Skin
-----------	--

REL (USA)	Long-term value: 24 mg/m ³ , 5 ppm Skin
TLV (USA)	Long-term value: 97 mg/m ³ , 20 ppm BEI
78-93-3 methyl ethyl ketone	
REL (USA)	Long-term value: 590 mg/m ³ , 200 ppm
REL (USA)	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV (USA)	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI
67-63-0 isopropyl alcohol	
REL (USA)	Long-term value: 980 mg/m ³ , 400 ppm
REL (USA)	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV (USA)	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI
Ingredients with biological limit values:	
67-64-1 Acetone	
BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
108-10-1 methyl isobutyl ketone	
BEI (USA)	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
108-88-3 Toluene	
BEI (USA)	1.2 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	1.3 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: <i>o</i> -Cresol with hydrolysis (background)
111-76-2 Glycol Ether EB	
BEI (USA)	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
78-93-3 methyl ethyl ketone	
BEI (USA)	2 mg/L Medium: urine Time: end of shift Parameter: MEK
67-63-0 isopropyl alcohol	
BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)

Hygienic protection:	Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.
Hand protection:	Protective gloves. The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles

Section 9: Physical and Chemical Properties

Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Boiling point:	-44 °C (-47 °F)
Flash point:	-19 °C (-2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion: exceeding 50	Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use. In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.7 Vol%
Upper Explosion Limit:	10.9 Vol%
Vapor pressure at 20 °C (68 °F):	8300.0 hPa (6226 mm Hg)
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapour density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octonal/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
VOC content:	963.7 g/l / 8.04 lb/gl
VOC content (less exempt solvents):	69.9%
Solids content:	8.1%

Section 10: Stability and Reactivity

Reactivity:	Stable at normal temperatures.
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

Section 11: Toxicological Information

LD/LC50 values that are relevant for classification:		
108-21-4 isopropyl acetate		
Oral	LD50	9800 mg/kg (rat)
108-10-1 methyl isobutyl ketone		
Oral	LD50	2100 mg/kg (rat)
Dermal	LD50	16000 mg/kg (rab)
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)
106-97-8 n-butane		
Inhalative	LC50/4 h	658 mg/l (rat)
64-17-5 ethyl alcohol		
Oral	LD50	7060 mg/kg (rat)
Inhalative	LC50/4 h	20000 mg/l (rat)
111-76-2 Glycol Ether EB		
Oral	LD50	1480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
78-93-3 methyl ethyl ketone		
Oral	LD50	3300 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rbt)
67-63-0 isopropyl alcohol		
Oral	LD50	4570 mg/kg (rat)
Dermal	LD50	13400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eye effects: Irritating effect.
Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)		
1	methyl isobutyl ketone	2
6	ethyl alcohol	1
1	Toluene	3
1	Glycol Ether EB	3
6	isopropyl alcohol	3
NTP (National Toxicology Program)		
None of the ingredients is listed.		

Section 12: Ecological Information (non-mandatory)

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Other information: Product does not contain CFC's.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

Section 13: Disposal Considerations (non-mandatory)

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

Section 14: Transport Information (non-mandatory)

UN-Number	UN1950
DOT	N/A
DOT	Consumer Commodity ORM-D Aerosols, flammable, containing substances in Division 6.1, Packing Group III 1950 Aerosols
ADR	
Transport hazard class(es):	
Class	2.1
Marine pollutant:	No
Special precautions for user:	Warning: Gases
EMS Number:	F-D,S-U
Quantity limitations	On passenger aircraft/rail: Forbidden On cargo aircraft only: Forbidden
ADR	
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
Item: IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
Packaging Group:	--
UN "Model Regulation":	UN1950, Aerosols, 2.3 (2.1)

Section 15: Regulatory Information

SARA Section 355 (extremely hazardous substances):	
None of the ingredients in this product are listed.	
SARA Section 313 (Specific toxic chemical listings):	
108-10-1	methyl isobutyl ketone
108-88-3	Toluene
111-76-2	Glycol Ether EB
78-93-3	methyl ethyl ketone
67-63-0	isopropyl alcohol

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:	
108-10-1	methyl isobutyl ketone

California Proposition 65 chemicals known to cause developmental toxicity:

108-88-3 Toluene
67-56-1 Methanol

CANADIAN ENVIRONMENTAL PROTECTION ACT:

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

EPA:		
67-64-1	Acetone	I
108-10-1	methyl isobutyl ketone	I
108-88-3	Toluene	II
111-76-2	Glycol Ether EB	NL
78-93-3	methyl ethyl ketone	I

Section 16: Other Information

Contact: Regulatory Affairs
Date of preparation / last revision 05/06/2015 / -

